



Product Data

RAPID LIG-C™

THINNER / FILTRATION CONTROL ADDITIVE

Description:

Rapid Lig-C™ is a chrome-free water-soluble form of processed North Dakota origin lignite (Leonardite) for use as a rheology stabilizer and fluid loss control additive in water-base mud systems.

Advantages:

- ⇒ Contains high amounts of solid humic acid.
- ⇒ Improves fluid loss control when used in lignosulfonates.
- ⇒ Effective in drilling muds up to 350° F (177° C).

Rapid Lig-C™ causticized lignite may be used in mud systems having a broad range of salinity, pH, calcium, and total solids. Rapid Lig-C™ is also an effective oil/water emulsion stabilizer.

Appearance	Fine Black Powder
Moisture Content	10% to 13%
PH	9.0 to 9.5
Solubility in Water	75% to 85%
Specific Gravity:	1.5

Recommended Treatment:

Normal Applications: 1 to 10 ppb

When using Rapid Lig-C™ with CLS, add 1 part Rapid Lig-C™ to 2 parts CLS for best results. Mix Rapid Lig-C™ at a uniform rate through a conventional jet hopper, mud suction pump, or directly to the pits.

Rapid Lig-C™ is generally unaffected by most commonly encountered mud contaminants, and is temperature stable to 350° F.

Handling:

Rapid Lig-C™ is packaged in 50 lb. bags, palletized and shrink-wrapped. This additive is also available packaged in super-sacks and in bulk.

P. O. Box 81277 ♦ Lafayette, Louisiana 70598
Tel: 337.291.2778 ♦ Fax: 337.291.2781

Recommendations given in this bulletin are based on tests believed to be reliable. However, the use of the information is beyond the control of Rapid Drilling Products, LLC and no guarantee, expressed or implied is made to the results obtained if not used in accordance with directions or established safe practice. The buyer must assume all responsibility, including injury or damage from the misuse of the product as such, or in combination with other materials. This bulletin is not to be taken as a license to operate under or recommendation to infringe any patent.